

ABP Group Ltd.

Tel: +86 132 4379 6553 (for Russian speaking client)

Tel: +86 188 1444 0836 (for English speaking client)

Skype: abv.kherson

ICQ: 274 298 020

QQ: 195 666 9266

Email: abp.europe@gmail.com

Email: abp.europe@hotmail.com

web: www.abpeurope.com

web: www.abp.com.hk/en




**Bank account**

Account: 801-300005-838
 Address: 1 Queen's Road Central, Hong Kong
 Beneficiary: ABP GROUP LIMITED
 Bank name: HSBC (HONG KONG)
 SWIFT CODE: HSBCHKHHHKH






Add: 3F, Building 26, The First Industrial Area, Fuyong, Bao'an District, Shenzhen City, Guangdong province, China

1.Offer Validity: 1 month. 2013-10-21







2.MOQ: 10 SETS; If less than 10sets order, unit price USD10.00 more. (Only MC91 unit price USD6.00 more)

Wired Super-Mini CCTV Camera						
<p>-Features: These are the smallest wired CCTV camera that have ever built in the world. It is super mini & thin size, lightweight, low power consumption, high resolution, high sensitivity, easy to install, operate and also easy to conseal.</p> <p>-Application: Use for Home and Business Security, Shops, Pubs and Restaurants, Building Sites, Warehouses, Vehicles, Boats, Marine Use, Sports use, Wildlife, Farms, Stables and Kennels, Surveillance and Covert use, Nursery and child care, Firearm.</p> <p>-Usage 1) CCTV cameras can be used directly with a standard TV/VCR or RCA video monitor; 2) To view more than one CCTV camera on your TV/VCR you will need a quad or multiplexer; 3) To view on your computer or laptop you will need a DVR card or USB; 4) A standalone system that records is a standalone DVR.</p>						
Image	Model#	Description	Unit price (MOQ: 10sets)	price term	Contents	
Mini CCTV Camera						
1		MC5910	SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F1.2 / 90 ° Dimensions (LXWXH) : 13.8 x13.8 x 21mm POWER SUPPLY: DC 3.3V-24V Both Auido & Video	US\$23,00	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
2		MC59B36	SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 3.6mm F2.0 / 90 ° Dimensions (LXWXH) : 14 x14 x 29mm POWER SUPPLY: DC 3.3V-24V Both Auido & Video	US\$23,00	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
3		MC59P36	SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 3.6mm F3.0 / 90 ° Dimensions (LXWXH) : 14 x14 x 20mm POWER SUPPLY: DC 3.3V-24V Both Auido & Video	US\$25,30	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1







4		MC5912P	<p>SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 12mm F3.0 / 30 ° Dimensions (LXWXH) : 14 x14 x 35mm POWER SUPPLY: DC 3.3V-24V Both Audio & Video</p>	US\$28,75	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
5		MC5945P	<p>SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 45mm F3.0 / 15° Dimensions (LXWXH) : 14 x14 x 43mm POWER SUPPLY: DC 3.3V-24V Both Audio & Video</p>	US\$31,05	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
6		MC5970P	<p>SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 70mm F3.0 / 8° Dimensions (LXWXH) : 14 x14 x 79mm POWER SUPPLY: DC 3.3V-24V Both Audio & Video</p>	US\$34,50	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
7		E50	<p>Pure Brass Peephole Viewer Camera for Door 13.8mm super small diameter, suitable to all doors SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 480TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : F1.2/90°</p>	US\$33,35	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
8		MCV8- IR850	<p>IR: 850nm /8m SENSOR : 1/4 CMOS SYSTEM: PAL/NTSC 728 (H) x576 (V) HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.00Lux/8m LENS & VIEW ANGLE : F1.2/90° Power supply :DC5V: (3.6-5V) Extended Cable: default 0.5m (Additional purchase for longer cable up to 50m: USD0.5/m)</p>	US\$36,80	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
9		MCV8- IR850 (12V)	<p>IR: 850nm /8m SENSOR : 1/4 CMOS SYSTEM: PAL/NTSC 728 (H) x576 (V) HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.00Lux/8m LENS & VIEW ANGLE : F1.2/90° Power supply :DC12V: (3.6-24V) Extended Cable: default 0.5m (Additional purchase for longer cable up to 50m: USD0.5/m)</p>	US\$37,95	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1







10		MCV8-IR940	<p>IR: 940nm / 5m SENSOR : 1/4 CMOS SYSTEM: PAL/NTSC 728 (H) x576 (V) HORIZONTAL RESOLUTION: 520TVL Excellent night vision of: 0.00Lux/5m LENS & VIEW ANGLE : F1.2/90° Dimensions (DXL) : 18mm x 32mm POWER SUPPLY: DC:3.6-5V 230mA IR Control: Light /On-Off /Self-Motion Extended Cable: default 0.5m (Additional purchase for longer cable up to 50m: USD0.5/m)</p>	US\$36,80	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
11		MCV8-IR940 (12V)	<p>IR: 940nm / 5m SENSOR : 1/4 CMOS SYSTEM: PAL/NTSC 728 (H) x576 (V) HORIZONTAL RESOLUTION: 520TVL Excellent night vision of: 0.00Lux/5m LENS & VIEW ANGLE : F1.2/90° Dimensions (DXL) : 18mm x 32mm POWER SUPPLY: DC:3.6-5V IR Control: Light /On-Off /Self-Motion Extended Cable:0.5m (Additional purchase for longer cable up to 50m: USD0.5/1m)</p>	US\$37,95	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
12		MCV8-LED	<p>LED Luminous intensity : 17600mcd SENSOR : 1/4 CMOS SYSTEM: PAL/NTSC 728 (H) x576 (V) HORIZONTAL RESOLUTION: 520TVL Excellent night vision of : 0.00Lux/5m LENS & VIEW ANGLE : 90° Dimensions (DXL) : 18mm x 32mm POWER SUPPLY: DC:3.6-5V LED Control: Light /On-Off /Self-Motion Extended Cable:0.5m (Additional purchase for longer cable up to 50m: USD0.5/1m)</p>	US\$36,80	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1 stand X1
13		MCV8-LED (12V)	<p>LED Luminous intensity : 17600mcd SENSOR : 1/4 CMOS SYSTEM: PAL/NTSC 728 (H) x576 (V) HORIZONTAL RESOLUTION: 520TVL Excellent night vision of : 0.00Lux/5m LENS & VIEW ANGLE : 90° Dimensions (DXL) : 18mm x 32mm POWER SUPPLY: DC12V: (3.6-24V) LED Control: Light /On-Off /Self-Motion Extended Cable:0.5m (Additional purchase for longer cable up to 50m: USD0.5/1m)</p>	US\$37,95	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1 stand X1
14		MC91	<p>SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 480TVL Excellent night vision of 0.05Lux/F1.2 LENS & VIEW ANGLE : F1.2 / 90 ° Dimensions (LXWXH) : 15.5 x 15.5 x 20mm POWER SUPPLY: DC3.6-24V DC12: 45mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$18,40	EX W/H	mini camera X1; RCA BNC cable X1; AC adapter DC5V:X1 stand X1







15		MC91A	<p>SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 480TVL Excellent night vision of 0.05Lux/F1.2 LENS & VIEW ANGLE : F1.2 / 90 ° Dimensions (DXL) : 18mm x 29mm POWER SUPPLY: DC3.6-24V DC12: 45mA VIDEO OUT: 1.0V p-p/75ohm AUDIO OUT: 1.0V p-p/1Kohm</p>	US\$19,55	EX W/H	mini camera X1; RCA BNC cable X1; AC adapter DC5V:X1 stand X1
16		MC91B18	<p>SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 480TVL Excellent night vision of 0.1Lux/F2.8 LENS & VIEW ANGLE : F2.8 / 170 ° Dimensions (LXWXH) : 15.5 x 15.5 x 23mm POWER SUPPLY: DC3.6-24V DC12: 45mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$20,70	EX W/H	mini camera X1; RCA BNC cable X1; AC adapter DC5V:X1
17		MC91AB18	<p>SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 480TVL Excellent night vision of 0.05Lux/F2.8 LENS & VIEW ANGLE : F2.8 / 170° Dimensions (LXWXH) : 15.5 x 15.5 x 26mm POWER SUPPLY: DC3.6-24V DC12: 45mA VIDEO OUT: 1.0V p-p/75ohm AUDIO OUT: 1.0V p-p/1Kohm</p>	US\$21,85	EX W/H	mini camera X1; RCA BNC cable X1; AC adapter DC5V:X1
18		MC91P36	<p>SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 480TVL Excellent night vision of 0.1Lux/F2.8 LENS & VIEW ANGLE : F2.8 / 90 ° Dimensions (LXWXH) : 15.5 x 15.5 x 20mm POWER SUPPLY: DC3.6-24V DC12: 45mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$23,00	EX W/H	mini camera X1; RCA BNC cable X1; AC adapter DC5V:X1
19		MC91AP36	<p>SENSOR : 1/4 CMOS SYSTEM: NTSC: 720x480 PAL: 720x576 HORIZONTAL RESOLUTION: 480TVL Excellent night vision of 0.05Lux/F2.8 LENS & VIEW ANGLE : F2.8/ 90 ° Dimensions (LXWXH) : 15.5 x 15.5 x 22.5mm POWER SUPPLY: DC3.6-24V DC12: 45mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$24,15	EX W/H	mini camera X1; RCA BNC cable X1; AC adapter DC5V:X1
20		MC900-V9	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F1.2 / 90 ° Dimensions (LXWXH) : 10.5 x 10.5 x 17.5mm POWER SUPPLY: DC3.6-5V 70mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$29,90	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1

21		MC900A-V9	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F1.2 / 90 ° Dimensions (LXWXH) : 10.5 x 10.5 x 20mm POWER SUPPLY: DC3.6-5V 75mA VIDEO OUT: 1.0V p-p/75ohm AUDIO OUT: 1.0V p-p/1Kohm</p>	US\$31,05	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
22		MC900D-V9	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 90 ° Dimensions (LXWXH) : 11.5 x 11.5 x 20mm POWER SUPPLY: DC3.6-5V 70mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$31,05	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
23		MC900D A-V9	<p>Mini CCTV Camera SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F2.0 LENS & VIEW ANGLE : 0.5mm F2.0 / 90 ° Dimensions (LXWXH) : 11.5 x 11.5 x 22.5mm POWER SUPPLY: DC3.6-5V 75mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$32,20	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
24		MC900D V9-12	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F1.2 /90 ° Dimensions (LXWXH) : 11.5 x 11.5 x 22.5mm POWER SUPPLY: DC:5-16V 35mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$32,20	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
25		MC900D A-V9-12	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F1.2 /90 ° Dimensions (LXWXH) : 11.5 x 11.5 x 26mm POWER SUPPLY: DC:5-16V 35mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$33,35	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
26		MC900D	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 55 ° Dimensions (LXWXH) : 11.5 x 11.5 x 15mm POWER SUPPLY: DC3.6-5V 70mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$31,05	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1

27		MC900D A	<p>Smallest HD & Night Vision Mini CCTV Camera</p> <p>SENSOR : 1/3 CMOS</p> <p>SYSTEM: NTSC: 656×492 PAL: 768×576</p> <p>HORIZONTAL RESOLUTION: 520TVL</p> <p>Excellent night vision of 0.008Lux/F2.0</p> <p>LENS & VIEW ANGLE : 0.5mm F2.0 / 55 °</p> <p>Dimensions (LXWXH) : 11.5 x 11.5 x 17mm</p> <p>POWER SUPPLY: DC3.6-5V 75mA</p> <p>VIDEO OUT: 1.0V p-p/75ohm</p> <p>AUDIO OUT: 1.0V p-p/1Kohm</p>	US\$32,20	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
28		MC900D- 12	<p>SENSOR : 1/3 CMOS</p> <p>SYSTEM: NTSC: 656×492 PAL: 768×576</p> <p>HORIZONTAL RESOLUTION: 520TVL</p> <p>Excellent night vision of 0.008Lux/F1.2</p> <p>LENS & VIEW ANGLE : 0.5mm F2.0 / 55 °</p> <p>Dimensions (LXWXH) : 11.5 x 11.5 x 21mm (smallest)</p> <p>POWER SUPPLY: DC:5-16V 35mA</p> <p>VIDEO OUT: 1.0V p-p/75ohm</p>	US\$33,35	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
29		MC900D A-E	<p>SENSOR : 1/3 CMOS</p> <p>SYSTEM: NTSC: 656×492 PAL: 768×576</p> <p>HORIZONTAL RESOLUTION: 520TVL</p> <p>Excellent night vision of 0.008Lux/F1.2</p> <p>LENS & VIEW ANGLE : 0.5mm F2.0 / 55 °</p> <p>Dimensions (LXWXH) : 11.5 x 11.5 x 17mm (smallest)</p> <p>POWER SUPPLY: DC3.6-5V 75mA</p> <p>VIDEO OUT: 1.0V p-p/75ohm</p> <p>AUDIO OUT: 1.0V p-p/1Kohm</p> <p>Cable length 1.5m; 10-50m for optional purchase-USD0.5/m</p>	US\$32,20	EX W/H	mini camera X1;
30		MC900	<p>SENSOR : 1/3 CMOS</p> <p>SYSTEM: NTSC: 656×492 PAL: 768×576</p> <p>HORIZONTAL RESOLUTION: 520TVL</p> <p>Excellent night vision of 0.008Lux/F1.2</p> <p>LENS & VIEW ANGLE : 0.5mm F2.0 / 55 °</p> <p>Dimensions (LXWXH) : 9.5 x 9.5 x 12mm (smallest)</p> <p>POWER SUPPLY: DC3.3-6V 70mA</p> <p>VIDEO OUT: 1.0V p-p/75ohm</p>	US\$29,90	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
31		MC900A	<p>SENSOR : 1/3 CMOS</p> <p>SYSTEM: NTSC: 656×492 PAL: 768×576</p> <p>HORIZONTAL RESOLUTION: 520TVL</p> <p>Excellent night vision of 0.008Lux/F1.2</p> <p>LENS & VIEW ANGLE : 0.5mm F2.0 / 55 °</p> <p>Dimensions (LXWXH) : 9.5 x 9.5 x 15mm (smallest)</p> <p>POWER SUPPLY: DC3.6-5V 75mA</p> <p>VIDEO OUT: 1.0V p-p/75ohm</p> <p>AUDIO OUT: 1.0V p-p/1Kohm</p>	US\$31,05	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
32		MC900- 12	<p>SENSOR : 1/3 CMOS</p> <p>SYSTEM: NTSC: 656×492 PAL: 768×576</p> <p>HORIZONTAL RESOLUTION: 520TVL</p> <p>Excellent night vision of 0.008Lux/F1.2</p> <p>LENS & VIEW ANGLE : 0.5mm F1.2 / 55 °</p> <p>Dimensions (LXWXH) : 9.5 x 9.5 x 18mm (smallest)</p> <p>POWER SUPPLY: DC6-24V 30mA</p> <p>VIDEO OUT: 1.0V p-p/75ohm</p>	US\$32,20	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1



33		MC493	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 55° Dimensions (LXWxH) : 16mmX16mmX10.5mm POWER SUPPLY: DC3.6-5V 70mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$19,55	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
34		MC493A	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 55 ° Dimensions (LXWxH) : 16mmX16mmX10.5mm POWER SUPPLY: DC3.6-5V 72mA VIDEO OUT: 1.0V p-p/75ohm AUDIO OUT: 1.0V p-p/1Kohm</p>	US\$20,70	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
35		MC493-12	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 55 ° Dimensions (LXWxH) : 16mmX16mmX10.5mm POWER SUPPLY: DC9-12V 70mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$20,70	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
36		MC493A-12	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 55° Dimensions (LXWxH) : 16mmX16mmX10.5mm POWER SUPPLY: DC9-12V 72mA VIDEO OUT: 1.0V p-p/75ohm AUDIO OUT: 1.0V p-p/1Kohm</p>	US\$21,85	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
37		MC495	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 3.6mm F2.0 / 90 ° Dimensions (LXWXH) : 24mm x 18mm x (15-25mm) POWER SUPPLY: DC3.6-5V 70mA VIDEO OUT: 1.0V p-p/75ohm</p>	LENS 90 ° USD20,7	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
38		MC495A	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 3.6mm F2.0 / 90 ° Dimensions (LXWXH) : 24mm x 18mm x (15-25mm) POWER SUPPLY: DC3.3-6V 72mA VIDEO OUT: 1.0V p-p/75ohm</p>	LENS 90 ° USD19	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1

39		MC495-12	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 3.6mm F1.2 / 90 ° Dimensions (LXWXH) : 24mm x 18mm x (15-25mm) POWER SUPPLY: DC9-12V 72mA VIDEO OUT: 1.0V p-p/75ohm</p>	LENS 90 ° USD21,85	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
40		MC495A-12	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 3.6mm F2.0 / 90 ° Dimensions (LXWXH) : 24mm x 18mm x (15-25mm) POWER SUPPLY: DC9-12V 72mA VIDEO OUT: 1.0V p-p/75ohm AUDIO OUT: 1.0V p-p/1Kohm</p>	LENS 90 ° USD23	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
41		MC901A	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 55 ° Dimensions (LXWXH) : 9.5 x 18 x 9mm POWER SUPPLY: DC3.6-5V 72mA VIDEO OUT: 1.0V p-p/75ohm AUDIO OUT: 1.0V p-p/1Kohm</p>	US\$31,05	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
42		MC901D	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 55 ° Dimensions (L x D x H): 22 x 12 x 6mm POWER SUPPLY: DC3.6-5V 70mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$32,20	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
43		MC908	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 90 ° Dimensions (D x L) : 15mm x 24mm (smallest) POWER SUPPLY: DC3.6-5V 72mA VIDEO OUT: 1.0V p-p/75ohm</p>	LENS 90 ° USD32,2	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
44		MC908A	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 90 ° Dimensions (D x L) : 15mm x 24mm (smallest) POWER SUPPLY: DC3.6-5V 72mA VIDEO OUT: 1.0V p-p/75ohm AUDIO OUT: 1.0V p-p/1Kohm</p>	LENS 90 ° USD33,35	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1

45		MC908-12	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 90 ° Dimensions (D x L) : 15mm x 24mm (smallest) POWER SUPPLY: DC12V 40mA VIDEO OUT: 1.0V p-p/75ohm</p>	LENS 90 ° USD33,35	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
46		MC908A-12	<p>SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.008Lux/F1.2 LENS & VIEW ANGLE : 0.5mm F2.0 / 90 ° Dimensions (D x L) : 15mm x 24mm (smallest) POWER SUPPLY: DC5-12V 40mA VIDEO OUT: 1.0V p-p/75ohm AUDIO OUT: 1.0V p-p/1Kohm</p>	LENS 90 ° USD34,5	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
47		MCV6-IR850	<p>IR: 850nm / 5m SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of 0.00Lux/5m LENS & VIEW ANGLE : 55° Dimensions (LXWXH) : 14.5 x 14.5 x 15.5mm POWER SUPPLY: DC:3.6-5V 200mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$34,50	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
48		MCV6-IR940	<p>IR: 940nm / 3m SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of: 0.00Lux/3m LENS & VIEW ANGLE : 55° Dimensions (LXWXH) : 14.5 x 14.5 x 15.5mm POWER SUPPLY: DC:3.6-5V 200mA VIDEO OUT: 1.0V p-p/75ohm IR Control- Light /On-Off /Self-Motion</p>	US\$34,50	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
49		MCV6-LED	<p>LED Luminous intensity : 12000mcd SENSOR : 1/3 CMOS SYSTEM: NTSC: 656x492 PAL: 768x576 HORIZONTAL RESOLUTION: 520TVL Excellent night vision of : 0.00Lux/5m LENS & VIEW ANGLE : 55 ° Dimensions (LXWXH) : 14.5 x 14.5 x 15.5mm POWER SUPPLY: DC:3.6-5V 180mA VIDEO OUT: 1.0V p-p/75ohm</p>	US\$34,50	EX W/H	mini camera X1; RCA/BNC cable X1; AC adapter X1
CCTV LENS						
50		CL3620B	<p>FORMAT: 1/3 MOUNT: M12*0.5 FOCAL LENGTH: 3.6 ANGEL OF VIEW: 90° LENS CONSTRUCTION: 4G</p>	US\$2,30	EX W/H	

51		CL2820B	FORMAT: 1/3 MOUNT: M12*0.5 FOCAL LENGTH: 2.8 ANGEL OF VIEW: 120° LENS CONSTRUCTION: 5G	US\$3,45	EX W/H	
52		CL2120B	FORMAT: 1/3 MOUNT: M12*0.5 FOCAL LENGTH: 2.0 ANGEL OF VIEW: 170° LENS CONSTRUCTION: 6G	US\$4,60	EX W/H	
53		CL2820P	FORMAT: 1/3 MOUNT: M12*0.5 FOCAL LENGTH: 2.8 ANGEL OF VIEW: 90° LENS CONSTRUCTION: 5G	US\$6,90	EX W/H	
54		CL3720P	FORMAT: 1/3 MOUNT: M12*0.5 FOCAL LENGTH: 3.7 ANGEL OF VIEW: 60° LENS CONSTRUCTION: 4G	US\$4,60	EX W/H	
55		CL5520F	FORMAT: 1/3 MOUNT: M8*0.2 FOCAL LENGTH: 0.5 ANGEL OF VIEW: 55° LENS CONSTRUCTION: 3G +1IR	US\$2,88	EX W/H	
56		CL5020	FORMAT: 1/3 MOUNT: M8*0.2 FOCAL LENGTH: 0.5 ANGEL OF VIEW: 55° LENS CONSTRUCTION: 3G	US\$2,88	EX W/H	
2.4Ghz Wireless transmitting						
57		MM102T	2.4GHz Wireless AV Transmitter Module usage: wired CCTV camera+ MM102T+wireless receiver Audio Subcarrier Freq : 6.0MHz Power: 100mW Transmssion range: 200 meters in line of sight Very small size: 9.5X25mm	US\$10,35	EX W/H	tranmitter module X1
58		MM100T	2.4GHz Wireless AV Transmitter Module usage: wired CCTV camera+ MM100T+wireless receiver Audio Subcarrier Freq : 6.5MHz Power: 100mW Transmssion range: 200 meters in line of sight Very small size: 18.5X18.5mm	US\$10,35	EX W/H	tranmitter module X1

Mini Audio Monitor

	Mini Audio Monitor					
59		MA200A	<p>Monitor Range:80~160 square meters Frequency Response:200Hz~10kHz Sensitivity:-60dB Output Impedance:600-1000 Ohm Non-equilibrium Voltage:DC 3.6-6V Current:5mA Size:L=14mm; D=4.2mm Weight:20g</p>	US\$7,48	EX W/H	SOUND PICKUP SERIES X1; RCA cable X1; AC adapter X1
60		MA200	<p>Monitor Range:80~160 square meters Frequency Response:200Hz~10kHz Sensitivity:-60dB Output Impedance:600-1000 Ohm Non-equilibrium Voltage:DC 3.6-6V Current:5mA Size:L=14mm; D=4.2mm Weight:0.2g</p>	US\$4,03	EX W/H	mini camera X1;